

Technical drawing of a mechanical part, likely a cross-section of a tapered shaft or a similar component. The drawing shows a central rectangular area with a cross-hatched pattern, indicating a specific material or a core. The dimensions and tolerances are as follows:

- Top horizontal dimension: $27,2_{-0,4}$
- Right vertical dimension: $13,6 \pm 0,5$
- Left side angles: $60^\circ \pm 30'$ and $30^\circ \pm 30'$
- Right side vertical dimension: $0,84^*$
- Bottom horizontal dimension: $27,2_{-0,4}$
- Bottom horizontal dimension: $36_{-0,6}$
- Right side vertical dimension: $11 \pm 0,3$

1. *Размеры для справок.
2. Покрытие: лак ЛБС-1 ГОСТ901-78.VI.УХ/4. Площадь покрытия 0,019м². Лак запечь по режиму: при температуре 60÷ 80°С – 1час, при температуре 130±10°С – 1час. Наплывы лака не допустимы.

					ВКИА.742176.084				
Изм./Лист	№ докум.	Подп.	Дата	Клин пазовый	Лит.			Масса	Масштаб
Разраб.	Масленникова	<i>Сидор</i>	02.11.17		01			0,135	1:1
Проб.	Крекнин	<i>[Signature]</i>	3.11.17						
Т.контр.	<i>Сидоренко</i>	<i>[Signature]</i>	7.11.17		Лист			Листов	1
Н. контр.	Ермоленко	<i>Ерм</i>	10.11.17	Стеклотекстолит СТЭФ 1с-15.0 ГОСТ12652-74					
Утв.	Мазур	<i>Маз</i>	8.11.17						